



ASSEMBLY INSTRUCTIONS
Model: TT4040

STEP 1
UNFOLD THE LEFT AND RIGHT CHAIR ASSEMBLIES FIG. 1.
INSERT (8) ¼-20 x 2 TRUSS HEAD BOLTS, NUTS AND WASHERS "C" TWO ON EACH SIDE. FIG. 2
SET THEM SIDE BY SIDE WITH THE ARM RESTS ON THE OUTSIDES.

STEP 2
ATTACH THE TABLE TO THE LEFT AND RIGHT CHAIR ASSEMBLIES USING (2) ¼ x 3 LAG BOLTS "B" AND (2) ¼-20 x 3 TRUSS HEAD BOLTS, NUT AND WASHERS "C" AND (2) #8 X 2 FLAT HEAD SCREWS "D" IN PRE-DRILLED HOLES.

STEP 3
ATTACH THE BOTTOM UMBRELLA SUPPORT TO THE LEFT AND RIGHT CHAIR ASSEMBLIES USING (4) #8 X 2 FLAT HEAD SCREWS "D". LINE UP BOTH UMBRELLA HOLES.

- (1) Left chair
- (1) Right chair
- (1) Table top
- (1) Umbrella support
- (1) Hardware pack

TOOLS NEEDED
PHILLIPS HEAD SCREWDRIVER
SCREW GUN IS REQUIRED
7/16 SOCKET DRIVER

LETTER	QTY.	DESCRIPTION
A	8	¼-20 x 2" TRUSS HEAD BOLTS
B	2	¼ x 3 LAG BOLTS
C	2	¼-20 x 3" TRUSS HEAD BOLTS
C	12	¼" FLAT WASHER
C	10	¼-20 LOCK NUT
D	6	#8 X 2 FLAT HEAD SCREWS

